



C: MAGICDEPOT.IE
A: Unit 15A Togher Industrial Estate, Cork T12 R201, Ireland
T: +353 (0) 89 242 93 68
E: contact@magicdepot.ie

PRODUCT – NP1245.06 SERIES

PRODUCT GROUP – Protective Tapes

Application:

Suitable for Acrylic Sheets, PMMA, & All Types of Glass, Fiber Glass Boards, GI Coils, uPVC Profiles & Doors, Sandwich Panels, Marble, Ceramics, painted Wood and Laminate.

Not suitable for Powder-Coated Aluminum Profiles.

NP1245.06 Series exhibits the special “Easy-peel” characteristic for the rapid removal of the film from high-gloss to semi-matt surface. The removal force is inversely proportional to the speed of removal.



PRODUCT SPECIFICATION:

Film Type	Polyethylene (LDPE) UV Treated
Color	Red
Average Thickness (A.S.T.M)	50 Mic
Adhesive Type	Acrylic Adhesive
Adhesion to Steel (A.S.T.M)	350gm/25.4mm (Gm/mm)
Longitudinal Tensile Strength (A.S.T.M)	>3.5kg/25.4mm (Kg/mm)
Transversal Tensile Strength (A.S.T.M)	>2.0kg/25.4mm (kg/mm)
Longitudinal Max Elongation (A.S.T.M)	>350 (%)
Transversal Max Elongation (A.S.T.M)	>570 (%)

(American Standard Test Method- A.S.T.M)

Storage & Utilization

The tape can be stored for 12 months in dry conditions in its original packaging. The film should be removed within 3 months from the date of lamination, particularly if the product has been exposed to outdoor ageing.

