

Belgaseal 600-310



PRODUCT DESCRIPTION

Belgaseal 600-310 is a high-quality, permanently elastic airtightness foil. It is highly suited to the airtight connection of all foils from the BelgaClima range to adjoining structural elements such as concrete, stone, wood, plaster, aluminium and PVC.

PRODUCT CHARACTERISTICS

- strong adhesive power on many substrates, such as concrete, stone, wood, plaster, aluminium and PVC
- no fixing or pressure strip required
- paintable
- permanently elastic
- can also be used on slightly damp (not wet!) substrates
- system component of the BelgaClima window sealing system with 10-year guarantee*, suitable for RAL-compliant window installation

* Subject to use of all BelgaClima system components, in accordance with the manufacturer's guidelines

AREA OF APPLICATION

Belgaseal 600-310 was developed for the permanent airtight adhesion of the various foils from the BelgaClima range to adjoining structural elements such as concrete, stone, wood, plaster, aluminium and PVC.

PROCESSING

The surfaces to which the foil is to be glued must be dry and free from oil, grease and dust. When gluing to window profiles made of aluminium or PVC, these must be thoroughly degreased. The foils may not be glued onto frozen substrates. Apply the glue in ridges of approx. 8mm in diameter and then press the foil to be glued down to create a layer of glue approx. 2 mm thick.

PACKAGING

Belgaseal 600 : 12 sausage packs of 600ml per box
Belgaseal 310 : 12 tubes of 310ml per box

CLEANING

Traces of glue on the skin can be removed with soap and water.

WASTE PROCESSING

Belgaseal residues may be disposed of with household waste. The local regulations must be observed.

TECHNICAL FEATURES

Permissible temperature after hardening	-30°C to +80°C
Processing temperature	+5°C to +40°C
Resistance to frost during transport	to -15°C
Estimate of net consumption per sausage pack	Ø5mm ≈ 30m Ø8mm ≈ 12m
Shelf life	12 months, store dry and frost-free in the unopened original packaging



SAFETY GUIDELINES

Based on available data and experience, the product is not a hazardous substance within the meaning of the Hazardous Substances Regulation and the relevant EC Directives. Nevertheless, we recommend observing the usual care and hygiene when handling chemicals.

SPECIAL INSTRUCTIONS

Please take into account our installation guidelines. It is the user's responsibility to determine whether the product is suitable for the application by carrying out tests.

LIABILITY

Our general terms and conditions of sale and guarantee apply. These may be viewed at www.belgaclima.be. This information sheet gives advice only, with no acceptance of liability. The processing instructions presented must be adapted to the actual environmental conditions. The user is required to verify suitability and possible use by carrying out tests in order to avoid failures, for which we take no responsibility. Subject to technical changes. The most recent version of this information sheet can be found at www.belgaclima.be.

Remark: The use of airtightness materials (foils, glue, adhesive tapes, gaskets) that are not part of the BelgaClima range in combination with our BelgaClima airtightness products invalidates any form of system guarantee. Any leaks that result from this lie completely outside our responsibility.

