

## TECHNICAL DATA SHEET

### ZAKU EWI SEALING TAPES



Foam	Unit of measure	Values	Tolerance	Standard
Type		impregnated flexible PUR-foam		
Colour		grey		
Density	kg/m <sup>3</sup>	75	( +/- 7,5 )	ISO 845
Tensile strength	kPa	≥ 150		PN-EN-ISO 1798
Tensile elongation	%	≥200		PN-EN-ISO 1798
<b>Adhesive</b>				
Type		acrylate (A)		
Coating weight	g/m <sup>2</sup>	min. 80		
Adhesion (180°)				PN – C 89259
after 20 min	N/25mm	25		
Liner		scrim		
Covering		2 sided silicone white paper		
<b>Product</b>				
Width	mm	5-10	(+/-0,5)	
	mm	11-19	(+/-0,6)	
	mm	20-960	(+/-1)	
Thickness before expansion	mm	2 ; 3 ; 4 ; 6 ; 8 ; 10	(+/-1)	
Length	m	12,5 ; 10 ; 8 ; 5,6 ; 4 ; 3,3	( +/- 0,05 )	
Adhesion (180°)				PN – C 89259
20 min	N/25mm	10		
24h	N/25mm	12		
Expansion		up to 5 times		
Air permeability		Class 2		
				PN-EN 1026:2001
Watertightness	Pa	up to 300		
				PN-EN 1027:2001

#### STORAGE

The items should be stored in dry, clean conditions (humidity up to 70%) in temperature from +10°C to +30°C.